

CHALLENGER QUICK



GENERAL DESCRIPTION

Optima Challenger barriers are designed to control the high flow of traffic and parking places. The ideal solution for heavy-duty service on the driveway (residential parking control) and intensive use (public parking control) even in peculiar and difficult climatic conditions.

SYSTEM SPECIFICATIONS

- ➔ Barrier can provides 1 second operation time (Open or Close time).
- ➔ Barrier can be controlled by Optima App on your IOS and Android mobile phones.
- ➔ Barrier cabinet is designed to IP 55 rating EN 60529 (British BS EN 60529:1992) standards.
- ➔ All component of the mechanism is manufactured on CNC machines.
- ➔ Barrier has the manual release feature.
- ➔ Arm is aluminum with a special elliptical like cross-section design.
- ➔ A special design barrier arm enables a safety gasket to be mounted under the arm.
- ➔ Red/Green led light above the aluminum barrier arm.
- ➔ A high torque AC motor is utilized in the barrier.
- ➔ All gears in the barrier are heat treated.
- ➔ Control electronics are mounted in an IP 67 proof plastic box.
- ➔ Low power consumption and silent running.
- ➔ Compatible with all access control systems.
- ➔ All control electronics manufactured by Optima.
- ➔ Closing the barrier can be utilized by the automatic time delay feature. Time delay can be adjusted between 5/10/15 seconds.

SECURITY SYSTEMS | CHALLENGER QUICK ELECTROMECHANICAL ARM BARRIERS

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

Between -15°, and + 65°C, %95 non-condensing humidity; 220V 50-60 Hz.

OPTIONAL ACCESSORIES

- ➔ Push button box (Raise/Lower/Emergency stop).
- ➔ Red/green traffic lights with steel pole.
- ➔ Flashing light (flashes while the arm is in motion).
- ➔ Safety photocell.
- ➔ Stand and casing for safety photocell.
- ➔ Pneumatic edge safety sensor.
- ➔ Dual vehicle safety loop detector.
- ➔ Radio receiver & antenna.
- ➔ Radio transmitter.
- ➔ Wrong way alarm.
- ➔ High speed alarm.
- ➔ Protection bar for barrier cabinet.
- ➔ Barrier skirt (aluminum).
- ➔ Stop sign in the middle of barrier arm.
- ➔ SCADA or any control system: It is possible to change and check the position of barrier with touch screen control panel, mobile devices (ios-android), computer, etc.

TYPE DESCRIPTION

- ➔ Challenger Quick 2.75m maximum arm length, opening time approximately 1 seconds.

optima®

SECURITY SYSTEMS | CHALLENGER QUICK ELECTROMECHANICAL ARM BARRIERS

MAIN BODY MEASUREMENTS

