

C100S



GENERAL DESCRIPTION

Optima C100S short glass gate turnstiles are suitable for installations where security and aesthetics are both main concerns. Typical installation areas are governmental, commercial and military buildings, office centers, hotels, etc.

SYSTEM SPECIFICATIONS

- Main body and lateral lids are AISI 304-grade stainless steel.
- Top cover and wings tempered glass.
- Lateral covers are removable for easy maintenance.
- Motor start and stop control is maintained by Optima PLC controller.
- Low power consumption and silent running.
- Compatible with all access control systems .
- Turnstile is equipped with an alarm system which senses forbidden and reverse direction passing.
- Turnstiles closes flaps by itself after adjusted time if a valid card is presented but person not passed.
- All the obstacles in the passage are sensed with photoelectric sensors.
- Indoor use only.

SECURITY SYSTEMS | C100S SWING SPEEDLANE TURNSTILE (SHORT FLAP)

SYSTEM SPECIFICATIONS

- ➔ Push button box.
- ➔ Logo print on the flaps.
- ➔ Card reader system.
- ➔ Digital Counter.
- ➔ Card reader mounting plate inside or on the turnstile.
- ➔ Card reader mounting plate with pedestal.
- ➔ Stainless steel railing.
- ➔ Uninterrupted power supply (UPS).
- ➔ SCADA or any control system: It is possible to change and check the position of turnstile with touch screen control panel, mobile devices (ios-android), computer, etc.

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

- ➔ Between -15°C and +65°C, 95% non-condensing humidity; 220-240 VAC, mono phase, 50-60Hz.
- ➔ Power Consumption 200 W (Max).

MAIN BODY MEASUREMENTS

